



THERMORY®
LEAVE A LASTING IMPACT



THERMORY SPRUCE CLADDING

A cost-effective sound-tight-knot feature cladding. Thermory Spruce is from Scandinavian forests and has been thermally modified by the worlds largest modifier, Thermory.

Thermory Spruce is a rot-resistant softwood that, once modified, is an attractive light golden-brown colour throughout the full thickness of the timber, if left uncoated Thermory Spruce will age to an attractive silver-grey. The original colour and tone can be preserved with a quality penetrating oil, or alternatively stained darker with a tinted oil.

Natural characteristics of Thermory Spruce include sound tight knots making it a superb alternative to Siberian Larch and knotty cedar.

- 20 year warranty
- Stable hardwood
- Chemical free
- Thermal modification uses heat & steam
- Lengths: 3.0m – 5.4m
- Grade: Sound tight knot
- PASS Product Assurance Documentation
- Environmental Product Declaration
- Factory Coating available
- Recommended Coating: Dryden Wood Oil, CD50
- Fixings: Stainless 316 Grade Cladding Nails or Cladding Screws
- Exterior Claddings, Panelling & Sarking, Soffit Linings, Joinery, Screening, Battens

 **TIMBERLINE**

enquiries@timberline.co.nz | 0508 337 446
www.timberline.co.nz